

Technical Specifications

TeamTec Incinerator OG120CW

The incinerator consist of a combustion chamber with burner unit, sludge burning equipment, and electric control panel, all assembled in one complete unit resting on four (4) feet or pads to be welded or bolted to the deck or platform. Flue gas damper and cooling fan are delivered as separate units to be installed in the flue gas duct or funnel.

Maker: **TeamTec AS**
 Type: **OG120C**
 Version: **CW**
 Edition: **2007**

Description	Measure	Unit of Measure
<i>Incinerator (dim.dwg 2006692)</i>		
Outer dimensions (L x W x H)	1013 x 1457 x 1834	mm
Total weight	1430	kg
Feeding door clear opening (W x H)	300 x 750	mm
Sluice feeder opening	N/A	mm
Sluice capacity	N/A	l/charge
Incineration thermal capacity	210/ 180,000	kW / kcal/h
Sludge oil burning capacity nominal (IMO spec.)	N/A	l/h
Solid waste capacity, batch load	200	l/charge
Solid waste continuous charging	N/A	kg/h
Water injection capacity	N/A	l/h
Negative pressure	5 - 20	mmW.C.
Outer skin temperature above ambient	15	°C
Working temperature combustion chamber	850 - 1150	°C
Max temperature combustion chamber	1200	°C
Working temperature flue gas	250-350	°C
Diesel oil viscosity (max)	13	cSt at 40°C
Diesel oil consumption when support burner is in operation 1 / 2 nozzles	10 / -	l/h
Diesel oil consumption when 2 support burners are in operation, 1 / 2 nozzles each	N/A	l/h
El. power consumption diesel oil heater	2.0	kW
Nominal total electrical power consumption	6.0	kW
Total rated electrical power consumption	7.0	kW
Recommended supply fuse	16	A
Burner air blower capacity, maximum	700	m ³ /h
Secondary air fan	N/A	m ³ /h
Steam or compressed air requirement (for sludge atomizing)	N/A	norm.m ³ /h / bar
Pipe connection steam or air (DN)	N/A	

Description	Measure	Unit of Measure
Pipe connection for diesel line (supply / return) (DN)	15	
Pipe connection for sludge oil line (supply / return) (DN)	N/A	
Pipe connection for bilge water (DN)	N/A	
Pipe connection for drain of spill collector (DN / BSP)	- / 1"	
Flue gas outlet dimension (DN)	200	
Minimum distance between flue gas outlet and first component on the flue gas line	2500	mm
Incinerator body colour	RAL 6019	
Control panel colour	RAL 7032	

<i>Flue gas damper (3007338)</i>		
Flange dimension inlet (from incinerator) (DN)	200	
Flange dimension outlet (fan side) (DN)	200	
Weight	20	kg
Colour (heat resist.)	Aluminium	

<i>Flue gas fan frequency converter (dim.dwg)</i>		
IP rating	N/A	
Maximum ambient temperature, no derating	N/A	°C

<i>Flue gas fan (dim.dwg 4007653)</i>		
Flue gas fan capacity, maximum	3 500	m ³ /h
Back pressure, maximum	100	mmW.C.
Separate starter recommended fuse	N/A	A
Rated power consumption from separate supply	N/A	kW
Flue gas duct dimension (inlet / outlet) (DN)	200 / 200	
Flue gas fan weight	175	kg
Flue gas fan outer dimensions (L x W x H)	863 x 856 x 800	mm
Colour (heat resist.)	Aluminium	

Revised October 2009